


FLOOD INSURANCE STUDY

WAVE
HEIGHT
ANALYSIS



22
TOWN OF
BRINY BREEZES,
FLORIDA
PALM BEACH COUNTY



MARCH 31, 1982



Federal Emergency Management Agency

COMMUNITY NUMBER - 120197

ANALYSIS OF WAVE HEIGHTS
FOR
TOWN OF BRINY BREEZES, PALM BEACH COUNTY, FLORIDA

FEDERAL EMERGENCY MANAGEMENT AGENCY

I

BEST DOCUMENT AVAILABLE

TABLE OF CONTENTS

	Page
1.0 <u>INTRODUCTION</u>	1
1.1 Background and Purpose.....	1
2.0 <u>INVESTIGATIONS</u>	2
2.1 Previous Studies.....	2
2.2 Data Collection and Review.....	2
2.3 Wave Height Analysis.....	3
2.4 Results.....	5
3.0 <u>FLOOD PLAIN MANAGEMENT APPLICATIONS</u>	5
3.1 Flood Boundaries.....	8
3.2 Base Flood Elevations.....	8
3.3 Velocity Zones.....	8
4.0 <u>INSURANCE APPLICATION</u>	9
4.1 Flood Hazard Factors.....	9
4.2 Flood Insurance Zones.....	9
4.3 Flood Insurance Rate Map.....	10
5.0 <u>OTHER STUDIES</u>	10
6.0 <u>REFERENCES</u>	10

FIGURES

Figure 1 - Transect Location Map.....	4
Figure 2 - Typical Transect Schematic.....	7

TABLES

Table 1 - Transect Locations, Stillwater Elevations, and Maximum Wave Crest Elevations.....	6
Table 2 - Flood Insurance Zone Data.....	11

EXHIBITS

Exhibit 1 - Flood Insurance Rate Map	
--------------------------------------	--

1.0 INTRODUCTION

1.1 Background and Purpose

The Federal Emergency Management Agency recently adopted recommendations by the National Academy of Sciences to include prediction of wave heights in Flood Insurance Studies for coastal communities subject to storm surge flooding, and to report the estimated wave crest elevations as the base flood elevations on Flood Insurance Rate Maps (FIRMs).

Previously, FIRMs were produced showing only the stillwater storm-surge elevations due to the lack of a suitable and generally applicable methodology for estimating the wave crest elevations associated with storm surges. These stillwater elevations were subsequently stipulated in community flood plain management ordinances as the minimum elevation of the first floor of new construction. Communities and individuals had to consider the additional hazards of velocity waters and wave action on an ad hoc basis. Because there has been a pronounced tendency for buildings to be constructed only to meet minimum standards, without consideration of the additional hazard due to wave height, increasing numbers of people could unknowingly be accepting a high degree of flood-related personal and property risk in coastal areas subject to wave action. Therefore, the Federal Emergency Management Agency has pursued the development of a suitable methodology for estimating the wave crest elevations associated with storm surges. The recent development of such a methodology by the National Academy of Sciences (Reference 1) has led to the adoption of wave crest elevations for use as the base flood elevations in coastal communities.

Since 1871, 12 hurricanes have passed through Palm Beach County. Among the more severe were the storms of September 1928, September 1947, October 1947, and August-September 1964. The hurricane of September 1928 is considered one of the most violent ever to strike Florida. The center of the storm smashed into the West Palm Beach area with winds in excess of 100 miles per hour. Nearly 95 percent of the commercial and residential property in the West Palm Beach area was damaged. High tides ranged from 8 feet in Lake Worth to 10 feet at Palm Beach. Severe wave action was responsible for the washout of several bridges crossing Lake Worth. The hurricane of October 1947 climaxed an extremely wet rainy season in which precipitation in the county ranged from 70 to 85 inches.

The Town of Briny Breezes is located on the open coast and is subject to flooding from tidal surges associated with hurricanes. The purpose of this study is to revise the FIRM for the Town of Briny Breezes to include the effects of wave action associated with flooding from the Atlantic Ocean at the open coast and at the Intracoastal Waterway.

2.0 INVESTIGATIONS

2.1 Previous Studies

Stillwater elevations for hurricane surges with 10-, 50-, 100-, and 500-year return periods were determined by Tetra Tech, Inc. for all areas of Palm Beach County and its incorporated communities inundated by tidal flooding. The 100-year stillwater elevations were used as base flood elevations for the previously published Flood Insurance Study for Briny Breezes (Reference 2).

These elevations were determined by the joint probability method (Reference 3). The storm populations were described by probability distributions of five parameters which influence surge heights. These parameters were central pressure depression (which measures the intensity of the storm), radius to maximum winds, forward speed of the storm, shoreline crossing point, and crossing angle. These characteristics were described statistically, based on an analysis of observed storms in the vicinity of Palm Beach County. Primary sources of data for the parameters were the National Weather Service (Reference 4); Cry (Reference 5); Ho, Schwerdt, and Goodyear (Reference 6); and, the National Hurricane Research Project (Reference 7).

A numerical hydrodynamic model of the region was used to simulate the coastal surge generated by any chosen storm (that is, any combination of the five storm parameters defined previously). By performing such simulations for a large number of storms each of known total probability, the frequency distribution of surge height can be established as a function of coastal location. These distributions incorporate the large scale surge behavior, but do not include an analysis of the added effects associated with much finer scale wave phenomena, such as wave height, setup, or runup. The astronomical tide for the region was statistically combined with the computed storm tide to yield recurrence intervals of total water level.

The stillwater elevations developed for the previous study were used for the wave height analysis presented herein.

This report is authoritative for purposes of the National Flood Insurance Program. Data presented herein supersedes all previous flood elevation determinations.

2.2 Data Collection and Review

All available source data applicable for the wave height analysis were collected and reviewed. Because wave height calculations are based on such parameters as the size and density of vegetation, natural barriers (such as sand dunes), buildings, and other manmade structures, it was necessary to obtain detailed information on the physical and cultural features of the study area.

Officials of the Town of Briny Breezes and Palm Beach County were contacted for maps and other possible data sources to be used in the analysis. In addition,

the Florida Department of Transportation; the Florida Department of Natural Resources, Bureau of Beaches and Shores; the U.S. Army Corps of Engineers, Jacksonville District; the National Ocean Survey; the U.S. Fish and Wildlife Service; the South Florida Water Management District; A.V. Strock and Associates; and Abrams Aerial Survey were contacted and all applicable data sources were obtained.

The principal source materials used for the wave height analysis are described below.


- a. Topographic data (ground elevations, seawall elevation, and locations of physical features) were determined using U.S. Geological Survey topographic maps at a scale of 1:24,000, with a contour interval of 5 feet (Reference 8); National Ocean Survey storm evacuation maps at a scale of 1:62,500, with a contour interval of 5 feet (Reference 9); and beach profiles of the immediate Atlantic coast area obtained from the Florida Department of Natural Resources (Reference 10).
- b. Stereoscopic aerial photography at a scale of 1:12,000 and National Wetlands Inventory Maps at a scale of 1:24,000 were used to determine vegetation and building parameters and to supplement the topographic maps for locations of physical features (References 11 and 12).

2.3 Wave Height Analysis

The methodology for analyzing the effects of wave heights associated with coastal storm surge flooding is described in the National Academy of Sciences report (Reference 1). This method is based on the following major concepts. First, depth-limited waves in shallow water reach a maximum breaking height that is equal to 0.78 times the stillwater depth. The wave crest is 70 percent of the total wave height above the stillwater level. The second major concept is that wave height may be diminished by dissipation of energy due to the presence of obstructions, such as sand dunes, dikes and seawalls, buildings, and vegetation. The amount of energy dissipation is a function of the physical characteristics of the obstruction and is determined by procedures prescribed in Reference 1. The third major concept is that wave height can be regenerated in open fetch areas due to the transfer of wind energy to the water. This added energy is related to fetch length and depth.

Wave heights were computed along transects (cross section lines) in accordance with the Users Manual for Wave Height Analysis (Reference 13). The transects were located along the coastline as shown in Figure 1. They were located with consideration given to the physical and cultural characteristics of the land so that they would closely represent conditions in their locality. Transects were spaced close together in areas of complex topography and dense development. In areas having more uniform characteristics, they were spaced at larger intervals. It was also necessary to locate transects in areas where unique flooding existed and in areas where computed wave heights varied significantly between adjacent transects.

Each transect was taken perpendicular to the shoreline and extended to the inland limit of tidal flooding. Along each transect, wave heights and elevations



4A




FIGURE 1

FEDERAL EMERGENCY MANAGEMENT AGENCY

PALM BEACH COUNTY, FL

APPROXIMATE SCALE



TRANSECT LOCATION MAP

BEST DOCUMENT AVAILABLE

were computed considering the combined effects of changes in ground elevation, vegetation, and physical features. The stillwater elevations for the 100-year flood were used as the starting elevations for these computations. Wave heights were calculated to the nearest 0.1 foot, and wave elevations were determined at whole-foot increments along the transects. The location of the 3-foot breaking wave for determining the terminus of the V Zone (area with velocity wave action) was also computed at each transect. Table 1 provides a listing of the transect locations and stillwater elevations, as well as maximum wave crest elevations in the vicinity of Briny Breezes.

Figure 2 is a profile for a typical transect illustrating the effects of energy dissipation and regeneration on a wave as it moves inland. This figure shows the wave elevations being decreased by obstructions, such as buildings, vegetation, and rising ground elevations, and being increased by open, unobstructed wind fetches. Actual wave conditions in Briny Breezes may not necessarily include all the situations illustrated in Figure 2.

After analyzing wave heights along each transect, wave elevations were interpolated between transects. Various source data were used in the interpolation, including topographic maps (References 8 and 9), beach profiles (Reference 10), and aerial photographs (Reference 11), along with engineering judgment. Controlling features affecting the elevations were identified and considered in relation to their positions at a particular transect and their variation between transects.

2.4 Results

Rapidly rising sand dunes and seawalls provide considerable protection along the open coast of Palm Beach County. These dunes and seawalls are expected to remain intact during the 100-year storm surge and are considered effective wave energy dissipators. The banks along the Intracoastal Waterway are protected by bulkheads. These bulkheads are capable of dissipating wave energy.

Only a small portion of Briny Breezes is affected by wave action. Wave heights greater than 3 feet associated with the 100-year storm surge on the Atlantic coast are diminished near the open coast by ascending ground slope and seawalls. The maximum wave crest elevation at the Atlantic Ocean shoreline is 10 feet.

Because of the narrowness of the Intracoastal Waterway in the vicinity of Briny Breezes, there is no wave generation across the waterway. Thus, this area is not affected by wave action.

3.0 FLOOD PLAIN MANAGEMENT APPLICATIONS

A prime purpose of the National Flood Insurance Program is to encourage local governments to adopt sound flood plain management programs designed to reduce future flood losses. The FIRM for Briny Breezes has been revised to incorporate the latest available information, including wave height data, to assist this community in developing the most appropriate and effective flood plain management measures.

Table 1.
Transect Locations, Stillwater Elevations, and Maximum Wave Crest Elevations

Transect	Location	Elevation (Feet NGVD)	
		Stillwater	Wave Crest
17	Ocean Ridge/Boynton Beach - From Atlantic coastline westward across Lake Worth to the limit of inundation by the 100-year storm surge; crosses State Highway 1A approximately 500 feet south of intersection with Sabal Island Drive in Ocean Ridge	7.0 ¹	11 ¹
18	Briny Breezes/Boynton Beach - From Atlantic coastline westward across the Intracoastal Waterway to the limit of inundation by the 100-year storm surge; crosses Old Ocean Boulevard near intersection with Hibiscus Drive in Briny Breezes	7.0 ¹	11 ¹
19	Gulf Stream - From Atlantic coastline westward across the Intracoastal Waterway to the limit of inundation by the 100-year storm surge; crosses Avenue Au Soleil at intersection with Indigo Point	7.0 ¹	11 ¹

¹Atlantic Ocean




FIGURE 2
TYPICAL TRANSECT SCHEMATIC

3.1 Flood Boundaries

In order to provide a national standard without regional discrimination, the 100-year flood has been adopted by the Federal Emergency Management Agency as the base flood for purposes of flood plain management. This flood has a 1 percent chance of being equalled or exceeded each year and is expected to be exceeded once on the average during any 100-year period. The risk of having a flood of this magnitude or greater increases when periods longer than 1 year are considered. For example, over a 30-year period, there is a 26 percent chance of experiencing a flood equal to or greater than the 100-year flood. The 500-year flood plain is also shown on the FIRM to indicate areas of moderate flood hazards.

Areas inundated by the 100-year flood are shown as A and V Zones on the community's FIRM. It is in these areas that the Federal Emergency Management Agency requires local communities to exercise flood plain management measures as a condition for participation in the National Flood Insurance Program.

3.2 Base Flood Elevations

Areas within the communities studied by detailed engineering methods have base flood elevations established in A and V Zones. These are the elevations of the base (100-year) flood relative to the National Geodetic Vertical Datum of 1929. In coastal areas affected by wave action, base flood elevations are generally maximum at the open coast shoreline. These elevations generally decrease in a landward direction at a rate dependent on the presence of obstructions capable of dissipating the wave energy. Where possible, changes in base flood elevations have been shown in 1-foot increments on the FIRMs. However, where the scale did not permit, 2- or 3-foot increments were sometimes used. Base flood elevations shown in the wave action areas represent the average elevation within the zone. Current program regulations generally require that all new construction be elevated such that the first floor, including basement, is above the base flood elevation in A and V Zones.

3.3 Velocity Zones

The U.S. Army Corps of Engineers (Reference 14) has established the 3-foot breaking wave as the criterion for identifying coastal high hazard zones. This was based on a study of wave action effects on structures. This criterion has been adopted by the Federal Emergency Management Agency for the determination of V Zones. Because of the additional hazards associated with high-energy waves, the National Flood Insurance Program regulations require much more stringent flood plain management measures in these areas, such as elevating structures on piles or piers. In addition, insurance rates in V Zones are higher than those in A Zones with similar numerical designations.

The location of the V Zone is determined by the 3-foot breaking wave as discussed previously. The detailed analysis of wave heights performed in this study allowed a much more accurate location of the V Zone to be established. The V Zone generally extends inland to the point where the 100-year flood depth is insufficient to support a 3-foot breaking wave.

4.0 INSURANCE APPLICATION

The assignment of proper actuarial insurance rates requires that frequency and depth of flooding be estimated as accurately as possible. Because waves can add considerably to expected flood depths, it is important that insurance rates consider this additional hazard. The Federal Emergency Management Agency has developed a process to transform the data from this study into flood insurance criteria. This process includes the determination of Flood Hazard Factors and the designation of flood insurance zones.

4.1 Flood Hazard Factors

The Flood Hazard Factor (FHF) is the device used to correlate flood information with insurance rate tables. Correlations between property damage from floods and their FHF are used to set actuarial insurance premium rate tables.

The FHF is shown as a three-digit code that expresses the difference between the 10- and 100-year flood elevations to the nearest 0.5 foot. For example, if the difference between water-surface elevations of the 10- and 100-year floods is 0.7 foot, the FHF is 005; if the difference is 1.4 feet, the FHF is 015; if the difference is 5.0 feet, the FHF is 050. When the difference between the 10- and 100-year water-surface elevations is greater than 10.0 feet, the FHF is computed to the nearest foot.

4.2 Flood Insurance Zones

After wave elevations for the 100-year storm surge were determined and mapped, the study areas were divided into zones, each having a specific flood potential and FHF. Each zone was assigned one of the following flood insurance zone designations:

Zone V8:

Special Flood Hazard Areas inundated by the 100-year flood, and that have additional hazards due to velocity (wave action); base flood elevations shown, and zones subdivided according to FHF's.

Zone A5:

Special Flood Hazard Areas inundated by the 100-year flood, with base flood elevations determined and zone designations assigned according to the FHF's.

Zone B:

Areas between the Special Flood Hazard Areas and the limits of the 500-year flood plain, including areas that are protected from the 100- and 500-year floods by dike, levee, or other water control structure; and areas subject to certain types of 100-year shallow flooding where depths are less than

1.0 foot, or where the contributing drainage area is less than 1 square mile. Zone B is not subdivided.

Zone C:

Areas not subject to flooding by the 500-year flood. Zone C is not subdivided.

Table 2, "Flood Insurance Zone Data," summarizes the FIFs, flood insurance zones, and base flood elevations for each flooding source in the study area.

4.3 Flood Insurance Rate Map

After flood insurance zones were established for the study area, the FIRM for Briny Breezes was revised to incorporate the new zone information. This map (Exhibit 1) contains the official delineation of flood insurance zones and base flood elevations.

In preparing the revised FIRM, updated topographic information was used to revise the open coast shoreline and some zone boundaries in areas not affected by the wave height analysis. Corporate limits were revised using a current community map (Reference 15).

5.0 OTHER STUDIES

FIRMS for the incorporated communities of Boynton Beach and Ocean Ridge and for Palm Beach County are being revised concurrently with Briny Breezes to include wave height analysis. The revised studies for these communities will be in agreement with this study.

6.0 REFERENCES

1. National Academy of Sciences, Methodology for Calculating Wave Action Effects Associated With Storm Surges, 1977
2. U.S. Department of Housing and Urban Development, Federal Insurance Administration, Flood Insurance Study, Town of Briny Breezes, Florida, 1978
3. U.S. Department of Commerce, Environmental Science Services Administration, Technical Memorandum WBTM Hydro 11, Joint Probability Method of Tide Frequency Analysis, V.A. Myers, April 1970
4. U.S. Department of Commerce, National Oceanic and Atmospheric Administration, National Weather Service, Tropical Cyclone Deck 993, 1975
5. U.S. Department of Commerce, Weather Bureau, Technical Paper No. 55, Tropical Cyclones of the North Atlantic Ocean 1871 - 1963, G.W. Cry, 1965

Table 2. Flood Insurance Zone Data

<u>Flooding Source</u>	<u>10-Year</u>	<u>Stillwater Elevation</u>		<u>500-Year</u>	<u>FHF</u>	<u>Zone</u>	<u>Base Flood Elevation (Feet NGVD) *</u>
		<u>50-Year</u>	<u>100-Year</u>				
Atlantic Ocean Open Coast	4.5	6.3	7.0	8.5	040	V 8	7 to 11
Intracoastal Waterway	4.7	6.6	7.3	9.0	025	A 5	7

*Due to map scale limitations, base flood elevations shown on the FIRM may represent average elevations for the zones depicted.

6. U.S. Department of Commerce, National Oceanic and Atmospheric Administration, Technical Report NWS-15, Climatological Characteristics of Hurricanes, F.P. Ho, R.W. Schwerdt, and H.V. Goodyear, July 1975
7. U.S. Department of Commerce, National Hurricane Research Project, Report No. 5, Survey of Meteorological Factors, March 1957
8. U.S. Department of the Interior, Geological Survey, 7.5-Minute Series Topographic Maps, Scale 1:24,000, Contour Interval 5 feet: Lake Worth, Florida (1945), Photorevised (1967), Photoinspected (1973)
9. U.S. Department of Commerce, National Oceanic and Atmospheric Administration, National Ocean Survey, Storm Evacuation Maps T-15056, Scale 1:62,500, Contour Interval 5 feet: West Palm Beach, Florida (1976)
10. Florida Department of Natural Resources, Bureau of Beaches and Shores, Palm Beach County, Florida, Beach Profiles, Scale 1:600, 1974
11. Federal Emergency Management Agency, Aerial Photography of Palm Beach County, Florida, Scale 1:12,000, March 1981
12. U.S. Department of the Interior, Fish and Wildlife Service, National Wetlands Inventory Maps, Scale 1:24,000: Lake Worth, Florida, (unpublished)
13. Federal Emergency Management Agency, Users Manual for Wave Height Analysis, Revised February 1981
14. U.S. Department of the Army, Corps of Engineers, Galveston District, Guidelines for Identifying Coastal High Hazard Zones, June 1975
15. Brockway, Weber & Brockway, Corporate Limits of the Town of Briny Breezes, Florida, Scale 1:1440, March 1963

U.S. Department of Housing and Urban Development, Federal Insurance Administration, Coastal Flooding Handbook, Parts I and II, Tetra Tech, Inc., May 1977